


Connection Units

Georgian Brass



Description

The elegantly styled range is manufactured from highly polished solid cast brass plates, with a brushed finish and is supplied in individual display boxes.

Features

- black or white inserts available
- matching metal rocker versions
- lockable fuse carrier for safety isolation
- captive fuse barrier
- clear white terminal markings
- colour coded terminals
- discreet neon versions
- neon leads enclosed
- 2 earth terminals
- captive and backed out terminals
- terminals have large lead-ins
- 25 year guarantee

Range

unswitched DP	1710
unswitched DP with flex outlet	1711
<i>plastic switch rockers</i>	
switched DP	1713
switched DP with neon	1714
<i>metal capped switch rockers</i>	
switched DP	2713
switched DP with neon	2714

- Prefix with insert colour

Technical Specification

voltage rating	250Vac
current Rating	13A
contact gap	3mm

no user serviceable parts, except BS 1362 fuse links

Back Boxes

minimum recommended depth

	Flush 25mm	Dry lining 35mm
1g	DB162	DB2540

Standards

- BS 1363 Part 4 as applicable

Terminal Capacity

	2.5mm ²	4mm ²	6mm ²	10mm ²
L & N	4	3	2	1

DETA

Kingsway House, Laporte Way
Luton, Beds LU4 8RJ

Tel. +44 1582 544 500 Fax: +44 1582 544 501
Technical Helpline +44 1582 544 548