


Plate Switches

Victorian Brass



Description

The elegantly styled range is manufactured from highly polished solid cast brass plates, with a brushed finish and is supplied in individual display boxes.

Features

- black or white inserts available
- metal capped rocker versions
- only one size 4mm screwdriver needed
- x-rated and can be used for switching inductive or fluorescent loads without de-rating
- clear white terminal markings
- captive and backed out terminals
- terminals have large lead-ins
- range can be expanded using Gridswitch range
- 25 year guarantee

Range

plastic switch rockers

10A 1g 2way	1603
10A 2g 2way	1604
10A 3g 2way	1605
10A 4g 2way	1620
Intermediate	1646

metal capped switch rockers

10A 1g 2way	2603
10A 2g 2way	2604
10A 3g 2way	2605
10A 4g 2way	2620
intermediate	2646

- Prefix with insert colour

Technical Specification

voltage rating	250Vac
current rating	10A
	X rated
contact gap	3mm

no user serviceable parts

Back Boxes

minimum recommended depth

	flush 25mm	dry lining 35mm
1-3g	DB162	DB2540
4g	DB163	DB2541

Standards

- BS EN 60669-1:2000

Terminal Capacity

	1mm ²	1.5mm ²	2.5mm ²	4mm ²
L	5	4	2	1

DETA

Kingsway House, Laporte Way
Luton, Beds LU4 8RJ

Tel. +44 1582 544 500 Fax: +44 1582 544 501
Technical Helpline +44 1582 544 548