


## Dimmer Switches



### Description

The elegantly styled Slimline Décor range is available in Chrome and Satin Chrome finishes, with either white or black insert colours.

Each product is supplied in its own polybag, protecting it up to the point of installation

### Features

- LED and incandescent / LV lamp versions available
- Metal capped knobs
- Protective film on frontplate prevents damage during installation
- Push on / push off control suitable for 2W circuits
- LED versions can be 2-way controlled using push-to-make switches
- Clear white terminal markings
- 2-year guarantee

### Technical Specification

|                           |  |
|---------------------------|--|
| Voltage rating            | 250Vac   |
| Frequency                 | 50Hz   |
| LED dimmers               | <ul style="list-style-type: none"> <li>• LED – 100W</li> <li>• Mains voltage</li> <li>• halogen – 200W</li> <li>• Incandescent and ECO halogen – 250W</li> </ul> |
| Incandescent dimmers      | 60-400W  |
| no user serviceable parts |  |

### Standards

- BS EN 60669 – 2 – 1
- BS 55014 – 1
- BS 55014 – 2

### Range

|                       |        |
|-----------------------|--------|
| <i>LED Dimmers</i>    |        |
| 1 gang 2-way 100W LED | SD1261 |
| 2 gang 2-way 100W LED | SD1262 |

|                                   |        |
|-----------------------------------|--------|
| <i>Standard Dimmers</i>           |        |
| 1 gang 2-way 60-400W incandescent | SD1253 |
| 2 gang 2-way 60-400W incandescent | SD1254 |

|                           |    |
|---------------------------|----|
| <i>Suffix finish with</i> |    |
| Chrome                    | CH |
| Satin Chrome              | SC |

### Back Boxes

|                           |               |                    |
|---------------------------|---------------|--------------------|
| Minimum recommended depth |               |                    |
|                           | flush<br>35mm | dry lining<br>35mm |
| 1g/2g                     | DB164         | DB2540             |

### Terminal Capacity

|   |                  |                    |
|---|------------------|--------------------|
|   | 1mm <sup>2</sup> | 1.5mm <sup>2</sup> |
| L | 2                | 1                  |