

LED Polycarbonate Half Lantern with PIR

To be read in full before installation and kept for future reference

Safety Instruction

- Ensure the power supply is switched off before fitting, servicing
- This lantern is for outdoor use only
- This lantern must be mounted on a non-flammable surface
- Ensure adequate ventilation is allowed between the lantern and any object above, in front or to either side. Minimum distance: 0.5m above, 0.3m to either side and 1.0m in front.
- This lantern is of Class II construction.
- This lantern must be installed in accordance with the current edition of the IEE Wiring Regulations.

If in doubt, contact a qualified electrician.

Installation Instructions

- Remove the front cover and diffuser by releasing the 2 retaining screws on the top and bottom of the fitting
- Feed the supply cable through the grommet and secure the body of the fitting to the mounting surface via the mounting holes using appropriate fixings, noting the correct “up” orientation
- Terminate the supply conductors into the terminal block ensuring the correct polarity is observed (L = Live (brown), N = Neutral (blue),
⊕ = Earth (green/yellow)).
- Remove the protective film from the reflector
- Insert the lamp into the lamp holder
- Return the front cover with diffuser back to the body and secure in place with the retaining screws removed earlier

Power Supply	220 - 240V 50Hz	Construction	Class II
Lamp Type	E27	PIR Detection Range & Angle	8 meters @ 120°
Lamp	9.5W 2800K LED	PIR Adjustments	None
IP Rating	IP44	PIR Manual override	No